

TYPE: PROJECT: CATALOG#: LED STRIP LIGHT





Product Features

The XID flexible strip light is a low voltage and high brightness slim profile ideal for a multitude of applications. Available in 5 meter rolls, can be cut to needed length and includes pre-applied double-sided adhesive for easy installation.

Product Specifications

Model	GS-50XID	GS-50XID2
Lumen Output	8640 lm (1728 lm/m)	
LED Quantity	1200	
Power Consumption (W)	96 W (19.2 W/m)	100 W (20 W/m)
Efficacy	90 lm/W	86.4 lm/W
Input Voltage	12V DC, 24V DC	
Colour Temperature (CCT)	3000K, 3500K, 4000K, 5000K	
Dimensions	5000 x 15 x 3.2 mm	5000 x 17 x 3.2 mm
CRI	Ra80	
IP Rating	IP20	IP65
Beam Angle	120°	

Technical Drawing



Order Form

GS	-	-	-	-
Series	2	3	4	5
2. MODEL	3. LENGTH	4. VOLTAGE	5. Colour Temperature	
XID XID XID2 XID2	50 5000 (5m)	A 12V DC B 24V DC	30 3000K 35 3500K 40 4000K 50 5000K	

Hardwire Power Supplies and Accessories

Part Name	Description
DR-CV-12W	12W Triac Dimming driver
DR-CV-20W	20W Triac Dimming driver
DR-CV-30W	30W Triac Dimming driver
DR-CV-40W	40W Triac Dimming driver
DR-CV-60W	60W Triac Dimming driver
DR-CV-80W	80W Triac Dimming driver
E40L	40W Triac Dimming driver
E60L	60W Triac Dimming driver
E96L	100W Triac Dimming driver
M150L	150W Triac Dimming driver
M200L	200W Triac Dimming driver
M300L	300W Triac Dimming driver



Dimmable Power Supply (DR-CV-XXW)



Dimmable Power Supply (M_XX)



Dimmable Power Supply (E_XXL)

Dimmable Drivers


Please see our driver catalog for more options.

Catalog


TYPE: PROJECT: CATALOG#: LED STRIP LIGHT

Quick Connectors

Part Name	Description
GS-ID-C3	Strip to Power Connector. Available in static colour and RGB
GS-ID-C1	Strip to Power 3" Connector. Available in static colour and RGB
GS-ID-C5	Strip to strip Coupler. Available in static colour and RGB
GS-L001	L Connector. Available in static colour and RGB
GS-T003	T Connector. Available in static colour and RGB
GS-ID-C4	+ Connector




Strip to Power Connector




Strip to Strip Connector




Static - 2 Wires




RGB - 4 Wires



L Connector



T Connector



+ Connector

Controllers

Part Name	Description
GC-2820WRGB	Wall mount RGB Controller. Touch screen RGB controller
GS-2822WCCT	Wall mount CCT Controller. Touch screen CCT controller
GC-2102DMX	DMX512 Decoder provides an addressable DMX signal to be used within a DMX controlled system
GX-2818RF	RGB wireless Controller. 10 preset modes
GC-1009-4V1	RGB wireless Decoder. Synchronization of multiple runs from one controller



Wall mount RGB Controller



DMX512 Decoder



RGB wireless Decoder