

TYPE:

PROJECT:

CATALOG#:


ROUND SQUARE DOWNLIGHT




## Product Features

The GP-SMC series is a modern and sleek design that offers a high transmittance lens along with a smooth, low glare light pattern with anti-glare design. This light will conveniently last over 50,000 hours and is suitable in wet locations. The option of dimming from 10% - 100% is also available.

## Technical Drawing



GP-05-SMC



GP-07-SMC

Units in Metric

## Product Specifications

Model	GP-05-SMC	GP-07-SMC
Lumen Output	800 lm	1200 lm
Power Consumption (W)	10.5 W	14.2 W
Input Voltage	120-277V AC	120-277V AC
Colour Temperature (CCT)	3000K, 3500K, 4000K	3000K, 3500K, 4000K
CRI	Ra 80, Ra 90	Ra 80, Ra 90
Dimensions (mm)	Ø 137 x 41.9	Ø 161 x 41.9
Beam Angle	90° ± 7°	90° ± 7°

## Order Form

GP	SMC	3	4	5	6	7	8	9
Series	Model							
<b>3. SIZE</b>	<b>4. VOLTAGE</b>	<b>5. CCT</b>	<b>6. HOUSING</b>	<b>7. CRI</b>	<b>8. DIMMING</b>	<b>9. IP</b>		
<b>05</b> 5"	<b>A</b> 120-277V AC	<b>30</b> 3000K	<b>BL</b> Black	<b>80</b> Ra80	<b>DM</b> 1-10V	<b>44</b> Damp Location		
<b>07</b> 7"		<b>35</b> 3500K	<b>WH</b> White	<b>90</b> Ra90	<b>TR</b> TRIAC	<b>65</b> Wet Location		
		<b>40</b> 4000K	<b>GR</b> Grey					