GS-NFX1V2

TYPE: **PROJECT:** **CATALOG#:** **LED STRIP LIGHT**

Product Features

- Slim, high-brightness LED strip with low voltage.
- Cuttable 5m rolls with adhesive backing for easy install.
- Available in single colors and RGB.
- Works in -40°C indoor & outdoor; L70, LM-80, LM-21 compliant.

IP20 IESNA LM-79 IESNA LM-80 5 YEARS LIMITED WARRANTY INCLUDED

Technical Drawing



Product Specifications

Model	GS-NFX1V2
Lumen Output	2,160 lm (432 lm/m)
LED Quantity	600 LEDs
Power Consumption	24 W (4.8 W/m)
Colour Temperature	2700K, 3000K, 3500K, 4000K, 5000K, Red, Green, Blue, RGB
Efficacy	90 lm/W
Input Voltage	24V DC
Dimension	5,000 × 8 × 3.2 mm
CRI	Ra90
Beam Angle	120°
IP Rating	IP20
Working Temperature	-20° ~ 40°C

Order Form

GS - NFX1V2 - ____ - ____ - ____ - ____ - ____ - ____ - ____

SERIES | MODEL | 3. LENGTH | 4. WATTAGE | 5. VOLTAGE | 6. CCT | 7. CRI | 8. BEAM

3. LENGTH

50	5,000 (5m)

4. WATTAGE

5	4.8 W/m

5. VOLTAGE

A	24V DC

6. CCT

27	2700K	**40**	4000K	**R**	Red
30	3000K	**50**	5000K	**G**	Green
35	3500K	**RGB**	RGB	**B**	Blue

7. CRI

R90	Ra90

8. BEAM

120D	120°

greenimagetech.com
105-8288 N Fraser Way
Burnaby BC, V3N 0E9
T: (604) 207-9879
F: (604) 207-6992
© Green Image Tech, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.

Plug-In Power Supplies and Accessories

Part Name	Description
ACDC24-12	24W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/12VDC.
ACDC48-12	48W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/12VDC.
ACDC96-12	96W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/12VDC.
ACDC24-24	24W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/24VDC.
ACDC48-24	48W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/24VDC.
ACDC96-24	96W Plug and Play power supply. Includes AC wall plug and play and female power output plug for easy installation. 120VAC/24VDC.
GS-ID-C8	DC strip to Power Connector

Plug and Play power supply

DC strip to Power Connector

105-8288 N Fraser Way
Burnaby BC, V3N 0E9

T: (604) 207-9879
F: (604) 207-6992

© Green Image Tech, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.

TYPE: **PROJECT:** **CATALOG#:** **LED STRIP LIGHT**

Hardwire Power Supplies and Accessories

Part Name	Description
GC-ECV	60W, 96W Triac Dimming driver
GC-FCVM	120W, 180W, 192W, 288W, 300W, 384W Triac Dimming driver
GC-FCV	30W, 60W, 96W, 100W, 120W, 150W, 200W, 300W Triac Dimming driver
GC-SCV	30W, 60W, 96W, 100W, 120W, 150W, 200W, 300W Triac Dimming driver
GC-SCVM	120W, 180W, 192W, 288W, 300W, 384W Triac Dimming driver

TRIAC Dimming LED Driver (GC-FCV, SCV, SCVM)

5 in 1 Dimming LED Driver (GC-FCVM)

Mini Constant Voltage Driver (GC-ECV)

105-8288 N Fraser Way
Burnaby BC, V3N 0E9

T: (604) 207-9879
F: (604) 207-6992

© Green Image Tech, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.

TYPE: **PROJECT:** **CATALOG#:** **LED STRIP LIGHT**

Quick Connectors

Part Name	Description
GS-ID-C3	Strip to Power Connector. Available in static colour and RGB
GS-ID-C1	Strip to Power 3” Connector. Available in static colour and RGB
GS-ID-C5	Strip to strip Coupler. Available in static colour and RGB
GS-L001	L Connector. Available in static colour and RGB
GS-T003	T Connector. Available in static colour and RGB
GS-ID-C4	+ Connector



Strip to Power Connector

Strip to Strip Connector



Static - 2 Wires



RGB - 4 Wires



L Connector



T Connector



+ Connector

105-8288 N Fraser Way
Burnaby BC, V3N 0E9

T: (604) 207-9879
F: (604) 207-6992

© Green Image Tech, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.

Controllers

Part Name	Description
GC-2820WRGB	Wall mount RGB Controller. Touch screen RGB controller
GS-2822WCCT	Wall mount CCT Controller. Touch screen CCT controller
GC-2102DMX	DMX512 Decoder provides an addressable DMX signal to be used within a DMX controlled system
GX-2818RF	RGB wireless Controller. 10 preset modes
GC-1009-4V1	RGB wireless Decoder. Synchronization of multiple runs from one controller

Wall mount RGB Controller

DMX512 Decoder

RGB wireless Decoder

105-8288 N Fraser Way
Burnaby BC, V3N 0E9

T: (604) 207-9879
F: (604) 207-6992

© Green Image Tech, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.