TL-300

Deployable portable lighting in one bespoke robust package.

Portable Light Tower

HIGHER, BRIGHTER, MORE STABLE

Expanding or retracting requires just two steps and can be completed in 10 seconds.

1 Release the legs



2 Release and rise the extension pole

Secure the lamp at any height with the buckle.



One-click release or lock of the legs.

Ground pegs are available to secure the light tower, providing wind and vibration resistance. (Optional)







HUMANIZED DESIGN HIDDEN IN THE DETAILS

USB Output

Dual rainproof USB outputs for charging two devices at once, rain or shine.



Phone Stand

Continue working while charging, the hook here can serve as a phone stand.

Stepless Dimming

Plug the driver into the rainproof port to unlock maximum brightness and stepless dimming.

LOWER CENTER OF GRAVITY, GREATER STABILITY.

Ultra-low center of gravity combined with extended legs effortlessly handles strong winds and slopes.

Ultra-low center of gravity greatly increases the stability of the lamp

Ultra-long working hours

Standard Mode Up To **13+** Hours
(D24-100 x2)

2 types of battery packs with different capacities have same contact slot.

D24-54 x 2

Typical working hours 36+ hours on Eco mode.

D24-100 x 2

Doubled typical working hours to 71+ hours.

Battery compartment fits
two replaceable battery packs.

High light efficiency illuminating a wider space

Equipped with high-brightness LED light source and high-quality optical lens system

AC Powered
Up To **14,000** LM

Battery-powered
Up To **8,000** LM

Stepless Dimmable (AC Powered)

0 — 14,000LM

4 Levels of Brightness (Battery Powered)

Eco	Balanced	Standard	Turbo
800LM	3000LM	5000LM	8000LM





Construction

Emergency

Sport

Maintenance



Infrastructure

Outdoor activities

Mining

Railway

Designed for single-person operation

Easy to grip and move,
weight 8.2 kg excluding battery pack.



Specifications

TL-300

Height	1.25m-3.1m
Weight	8.2KG (Fitting only)
Power Supply	D24 series battery pack / AC 100-277V
Lumens	0-14000Lm
Run Times	>13h10mins (Standard mode, D24-100 x 2)
IP Grade	IP66
Output(USB)	5V 2A
Operating Temp	-10℃-50℃

Size (mm)



Package

Model	TL-300
Size of Carton	1350x290x380mm
Gross Weight of Carton	10.5KG
PCS/Carton	1